


		LOADER PERFORMANCE Standard GP Bucket Capacity	Challenger With Link Bracket 1.26 cu.m	Challenger Without Link Bracket 1.26 cu.m	
	1	Dump Height	2.96 m	2.96 m	
	J	Load Over Height	3.39 m	3.39 m	
	Κ	Pin Height	3.61 m	3.61 m	
	L	Pin Forward Reach	0.42 m	0.42 m	
	M	Reach at Ground	1.60 m	1.47 m	
	Ν	Reach at full height	1.42 m	1.28 m	
	0	Reach at full Height bkt Dumping	1.1m	0.89m	
	Ρ	Below ground level DIG Depth	0.08m	0.1m	
	Q	Roll back at Ground	50 °	49 °	
	R	Dump Angle	45 °	45 °	
		Bucket Break-out Force	8183 kgf		
		Loader Arm Break-out Force	5315 kgf		
		Pay Load	2200 kgf		
		Lifting Capacity At Loader Arm Hook Pin	2600 kgf		

	EXCAVATOR PERFORMANCE	Challenger STANDARD		
	Standard GP Bucket Capacity	0.26 cu.m		
Α	Maximum DIG depth	4.77 m	15 ft-7.7in	
В	Reach Ground Level to Rear wheel center	6.77 m	22 ft-2.53in	
С	Reach at Ground level to slew center	5.47 m	17 ft-11.35in	
D	Reach at full height to slew center	2.82 m	9 ft-3in	
F	Maximum working height	5.98 m	19 ft-7.4in	
G	Maximum Load over Height	4.19 m	13 ft-9.3in	
Н	Bucket Rotation angle	201°		
	Bucket Tear out force	5936 kgf		
	Dipper Tear out force	3109 kgf		



CH 76
d
le 9.18
6.37
aked
le 11.56
8.76
CITY CH 76
115Ltr

ENGINE

Ashok Leyland H4CSE5520 BS-V (CEV)

Diesel Engine (3840 cc) Aspiration: **Turbocharged**

Gross power: 55 HP (40.5kW) @ 2000 rpm

Gross torque: 290Nm @ 1200rpm

TYRES

HYDRAULICS

Pump type: Load Sensing

Variable Piston Pump

Pressure : 3335 p.s.i (230 bar) Pump Flow : 108 lpm @ 2000 rpm

119 lpm @ high rpm

WEIGHT

2WD-8010 Kgs (Standard Bucket)

DRIVE

2 Wheel Drive

TRANSMISSION

CARRARO - 2WD Synchro-shuttle Transmission with integral torque convertor

STEERING

Power Steering

ELECTRICAL

12V Battery Systems (150Ah)

SPEED

Forward Max: 36 Km/Hr

Reverse Max : 9.3 Km/Hr (2nd gear)

BACKHOE BUCKET OPTIONS

Excavator Standard bucket: 0.26 cu.m

Trench bucket



TILTABLE STEERING



ROPS FOPS ON FULL CABIN



COMFORTABLE SEAT AIR CUSHION (Optional)



OIL IMMERSED 3 DISC RAPID FILL BRAKE SYSTEM



TALLEST DUMPING BACKHOE LOADER



BULL INFOMATICS



POWDER COATED MACHINE



HEAVY DUTY STEEL KING POST

BULL

THE TRUE ALL ROUNDER

INTERCHANGEABLE BUCKET ATTACHMENTS





ENGINE ASHOK LEYLAND H4CSE5520 BSV(CEV) Diesel Engine 3840 CC Aspiration: Turbocharged



HYDRAULIC PUMP AS MODE

Road | Loader | Eco | Power mode **Auto Sensing**

Backhoe

Automatic vehicle senses the different mode requirement (R | L | E | P) based on the demand of workload.



SMART SENSING VALVES State of the Art loading sensing high efficiency valves.

RAPID SERVICE Closed only after your OTP



5000 ENGINE WARRANTY HOURS OR

ENGINE WARRANTY YEARS

SERVICE CHARGES

- * Engine warranty is subject to whichever condition occurs
- ** Service charges depend on consumables and the service policy provided by Bull Machines. Please read the policy carefully before proceeding.

SQUARE CUT 90° FOUNDATION BUCKET



- Perfect square cut bucket
- No manual trim No man power problem



Specifically designed for civil foundation pits and water tanks, septic tank, trenches.









BULL MACHINES PVT.LTD,

S.F. No 41, Kangayampalayam Post, Trichy Road, Sulur, Coimbatore - 641 401, INDIA

Sales

□ : +91 98422 87770

International sales

☐ : exports@bullmachine.com ☐ : 88832 88832

Service and Spares

Dealer:			

www.bullindia.com